

Steamer Metos Marvel E2



Product information

SKU	4222852
Product name	Steamer Metos Marvel E2
Dimensions	1385 × 900 × 1520 mm
Weight	360,000 kg
Capacity	8 x GN1/1-65 / 6 x GN1/1-100
Technical information	400/230 V, 80 A, 51,4 kW, 3NPE, 50 Hz CW: 1/2" Drain: ø 1"

Description

Double chamber Metos Marvel pressure steamer E2 is a fast and efficient tool for lunch and à la carte production in modern professional kitchens. Metos Marvel pressure steamer cooks, defrosts and regenerates all types of food products, including delicate items.

Thanks to Metos Marvel's speed and efficiency you can prepare a meal just before serving it, thus ensuring its freshness. Gentle and healthy steam cooking retains the texture, nutrients and colour of the products. Additional portions made of various ingredients can be prepared quickly, as Metos Marvel needs no preheating. Many dishes can be cooked simultaneously without the flavours transferring from one food to another. Its ease-of-use with built-in programmes improves the efficiency and competitiveness of every kitchen.

Exact cooking control with 1°C precision or a core temperature probe placed in the product speed up the process and prevent overcooking. Cooking temperature range is 40-120°C (low-temperature cooking/thaw



40-80°C, normal cooking 80-100°C, express pressure cooking 100-120°C). Main menu offers two pre-set settings: 0.5 and 1 bar. Delta-T cooking allows you to define the temperature difference between the compartment and the inside of the product. Especially useful for cooking sensitive or hard foods.

Coloured, informative touch screen is large and easy to read. Core temperature, compartment temperature and remaining cooking time are clearly displayed. Large, intuitive touch symbols make the steamer quick and effortless to use. Your own programmes can be easily saved and selected. Memory space for up to 10,000 programmes. Timing option 0-99 hours with 1 second precision. Favourites list for easier, faster use.

Favourite programmes are available on the main screen menu.

Advanced safety equipment and monitoring technology make the cooker safe to use. Thanks to the advanced safety locking system, the door is quick to open and to close. The door cannot be opened if the compartment is under pressure or a programme is running (can be discontinued, if necessary). Handle is ergonomic and insulated and it's easy to use with one hand. Water dripping from the door and containers is collected in a drip pan..

- two chambers
- completely stainless steel, chambers of acid resistant steel
- removable guide rail rack with 6 rail pairs in both chambers, machine washable
- capacity 8 x GN1/1-65 mm (guide distance 103 mm) or 6 x GN1/1-100 mm (guide distance 128 mm)
- top loading height 1280 mm
- large and clear touch screen
- quick favourite program list
- pre-set buttons for 0.5 and 1 bar
- cooking with core temperature probe
- Delta-T cooking
- several alarms to choose to indicate completed cooking
- sounds can also be set product-specifically
- adjustable volume level and length
- display power save mode and screen lock
- integrated USB port for downloading programmes and updates
- USB also for saving HACCP data
- door safety locking system
- automatic alerts for controlled safety device testing
- diagnostic function
- maintenance easily from front or top

DELIVERY INCLUDES:

- removable guide rail rack
- core temperature probe