

Cold basin trolley Metos SPA/K-3 DW



Product information

SKU	4235041
Product name	Cold basin trolley Metos SPA/K-3 DW
Dimensions	719 × 1199 × 900 mm
Weight	67,000 kg
Capacity	3 × GN 1/1-200 or smaller
Technical information	230 V, 1.3 A, 0,2 kW, 1NPE, 50 Hz
Type of the refrigerant	R134a
Quantity of refrigerant [g]	200
Cooling capacity [W]	300

Description

Mobile bain marie with active static cooling for transport and delivery of cold dishes in GN containers or of individually packaged cold meals and drinks.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. Closed design with a seamless and jointless welded and fully insulated pan. Pan holds a GN 1/1-200 or smaller container. Residue-free emptying of well, thanks to special inclination of base, using 1/2" ball valve to be operated from the exterior. Drain tap protected against inadvertent opening, setting can easily be seen even from a distance. Active cooling by cooling aggregate located underneath the pan; cooling unit comprises CFC-free refrigerant and all-round tubing to ensure a high cooling capacity. Electronic



temperature control with fixed settings made at the factory, frontal operation using On/Off switch with integrated indicator light. Current supply on the underside of cooling aggregate via dimensionally stable and extractable spiral cable with angle plug and hanger. Welded frame rack made of square tubes with welded, continuously-folded shelf with continuous profile edge in trolley base. Four massive polyethylene disc bumpers at the bottom and two polymer corner bumpers at the upper corners of the structure that serve as bumpers and very effectively protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Trolley runs on 4 swivel casters of which 2 with total locks, ø125 mm, with pin fastening.

- 1 basin, dimensions 510 mm * 955 mm
- isolated
- 4 wheels, of which 2 lockable, wheel dimension 125 mm
- load capacity 225 kg
- with compressor cooling 6°C