

## Chilled display Metos Gastro GE-112-87-E



## **Product information**

SKU 4321340

Product name Chilled display Metos Gastro GE-112-87-E

Dimensions  $1125 \times 695 \times 870 \text{ mm}$ 

Weight 295,000 kg Capacity 3x GN1/1

Technical information 230 V, 10 A, 0,659 kW, 1NPE, 50 Hz Drain: ø 30

mm

Type of the refrigerant R134a

## **Description**

Metos Gastro GE-112-87-E is a recessable into furniture, seller-served chilled display, designed for use under demanding conditions, with a width of 1125 mm and height of 870 mm. The simple angular shape of the chilled display highlights the products being sold.

The display's tempered glass side panels, the glass shelf and the bright LED lighting for shelves and the cold tub make products being sold highly visible. In addition, the front glass of the display serviced by the seller provides a panoramic view of the products inside. The seller's side is equipped with handy sliding doors. The glass shelf can be regulated +/-25 mm and can be angled, which simplifies product selection. A 215 mm adjustable height cooled tub with Gastronorm dimensioning.



A great deal of attention has been paid to simplifying the cleaning of the Metos Gastro GE-112-87-E display. The display portion lacks virtually any seams and is easy to wipe clean. The tub's plates, which are made of stainless steel, can be removed and lifted up in order to clean the evaporator element. In addition, the display is equipped with an auto-defrost function, and a defrost water evaporation.

The display is equipped with air cooled chilling, digital temperature control and ventilator speed regulator. Temperature can be regulated between +4 °C...+12 °C. The front glass, side glass panels and the glass shelf are made from tempered glass. The substructure is made from stainless steel and insulation is polyurethane.

- recessable into furniture (cut out size 1065 x 670 m)
- shelf and tub lighting
- · tempered front glass, side panels and shelf
- sales space 1,6 m2
- temperature can be regulated between +4 °C...+12 °C.
- climate class 3M2
- digital temperature regulation
- ventilator speed regulator

## EXTRA ACCESSORIES (can be ordered separately):

- base; MG4000243 (Open stand), MG4321372 (Tubular body stand)
- price tag frame;
- bread frame;
- ancillary space;
- door locks;
- · central motor model