

Chilled display Metos Gastro OE-177-53-E



Product information

SKU	4321352
Product name	Chilled display Metos Gastro OE-177-53-E
Dimensions	1775 × 695 × 530 mm
Weight	270,000 kg
Technical information	230 V, 10 A, 0,758 kW, 1NPE, 50 Hz Drain: ø 30 mm
Type of the refrigerant	R404A

Description

Metos Gastro OE-177-53-E is a recessed, self-service chilled display designed for use under demanding conditions, with a width of 1775 mm and height of 530 mm. The simple angular shape of the chilled display highlights the products being sold.

The display's tempered glass side panels, the glass shelf and the bright LED lighting for shelves and the cold tub make products being sold highly visible. The self-service display is temptingly open on the customer side, with a hinged glass door on the seller's side. The glass shelf can be regulated +/-25 mm and can be angled, which simplifies product selection. A 215 mm adjustable height cooled tub with Gastronorm dimensioning.

A great deal of attention has been paid to simplifying the cleaning of the Metos Gastro OE-177-53-E display. The display portion lacks



virtually any seams and is easy to wipe clean. The tub's bottom plates, which are made of stainless steel, can be removed and lifted up in order to clean the evaporator element. In addition, the display is equipped with an auto-defrost function, the melting water from which is directed to the grey water system. For those installation locations where it is not possible to connect the display to the grey water system, an evaporation tank is included as an accessory.

The display is equipped with air cooled chilling, digital temperature control and a fan speed regulator. Temperature can be regulated between +4 °C...+12 °C. The glass side panels and glass shelf are made from tempered glass. The substructure is made from stainless steel and insulation is polyurethane.

- display with air curtain
- recessable into furniture (cut out size 1715 x 670 mm)
- shelf and tub lighting
- tempered glass side panels and shelf
- sales space 1,35 m²
- temperature can be regulated between +4 °C...+12 °C.
- climate class 3H1
- digital temperature regulation
- ventilator speed regulator

EXTRA ACCESSORIES (can be ordered separately):

- base; MG4321374 (Open stand), MG4000233 (Tubular body stand)
- price tag frame;
- bread frame;
- ancillary space;
- door locking;
- evaporation tank; MG4231377 (Manual), MG4231373 (Electronical 1000 W)
- central motor model.