

## Cold counter Metos Proff Eco NT-800-DSL-MU



### Product information

SKU	4334020
Product name	Cold counter Metos Proff Eco NT-800-DSL-MU
Dimensions	800 × 650 × 900 mm
Weight	71,020 kg
Capacity	1 x GN-sized cold cabinet
Technical information	220-240 V, 10 A, 0,37 kW, 1NPE, 50 Hz
Energy class	B <a href="#">Energy class certificate</a>
Type of the refrigerant	R290
Quantity of refrigerant [g]	80

### Description

Cold cabinet Metos Proff NT-800-DSL-MU serves as a handy work table while offering the ingredients within arm's reach. Metos Proff refrigeration and dispensing equipment are designed for different purposes of the professional kitchens and can function as separate units as well as the complete sets of distribution lines. Convertibility, easy-to-operate elements, seamless connectivity of the furniture and equipment and last but not the least, their hygiene, ergonomics and easy cleaning - these are the features that Proff-equipment brings to your kitchen.

Metos Proff NT-800-DSL-MU cool cabinet has one GN-measured refrigerated cabinet with one adjustable grid shelf. The unit has a left-hand door.

The device is made of stainless steel and has a smooth, insulated neutral countertop with a rounded front edge. The temperature adjustment



range of the refrigerator is from +3° to +10°C. The cast urethane insulation keeps the cool air inside the device and the efficient cooling fan distributes the air evenly all over the drawer. Cool cabinet has an electronic control with a digital temperature display. The control panel is retracted and thus protected from any collisions.

Thanks to the stainless steel countertop and rounded inner corners of the device the cleaning is very easy. Ergonomic and smooth surface with plastic handles can be easily kept clean. Removable and washable filter at the front part of the condenser keeps the cool air inside the device clean and at the same time prevents the device from getting dirty. The device has an automatic defrosting and evaporation of the meltwater, as well as a standard drainage possibility. Door gasket can be replaced without any tools. The cool cabinet is supplied with connectors for power cables at the bottom of the device, making it easier to keep the floor under the device clean.

- one GN-measured cabinet
- temperature adjustment range is +3°... +10°C
- digital temperature screen
- electronic control
- stainless steel structure
- cast urethane gasket
- removable and washable condenser filter
- automatic defrosting and evaporation of meltwater
- easy-to-change gaskets
- nondetachable refrigerator at the right side of the device
- adjustable feet +20...-45 mm
- refrigerant R290

#### THE DELIVERY INCLUDES:

- 1 grid shelf + 1 pair of runners/ cabinet
- connectors for power cables

#### ACCESSORIES (to be ordered separately):

- grid shelf (code: 4188723)
- shelf (code: 4188748)
- runners pair (code: 4321308)
- wheels (code: 4321300)
- connectable device for the central hook piece
- Brine-cooled device