

Combi kettle Metos Proveno 4G 80E



Product information

SKU	4224304
Product name	Combi kettle Metos Proveno 4G 80E
Dimensions	1154 × 720 × 900/1535 mm
Weight	230,000 kg
Capacity	80 L
Technical information	400/230 V, 40 A, 22 kW, 3NPE, 50/60 Hz CW: R½" (Ø15) HW: R½" (Ø15)

Description

Proveno 80: gross vol. 91 l, net vol. 80 l, boiling space 11 l

Metos Proveno is a Finnish-made smart mixing combi-kettle. Reliable automation ensures routine food production without constant care or monitoring. Programming and management of recipes is easier than ever with the help of time-saving audio-visual communications features. Metos Proveno can be customised according to the user needs with the help of the respective features and accessories. Optimal ergonomics, ease of use and effortless cleaning make the hygienic and energy-saving Metos Proveno a user-friendly and economical option.

Both fixed and free-standing (optional) installation is possible.

The control panel of the Metos Proveno is fully raised with a highly visible and easy-to-read digital interface which is protected from



knocks as well as steam rising from the kettle. All parts that become dirty in everyday use such as, for example, mixers and scrapers, are easily removable without any special tools and are dishwasher-safe. The sturdy stainless-steel lid has a Safety Grid Lid to facilitate adding of raw ingredients. Room for chef's tools is available on the control pillar top.

An automatically filled steam jacket means that the steam kettle is filled with water independently. It is possible to group Metos Proveno 4G combi-kettles by connecting them to other Metos 4G kettles and fixed Proveno 2G and 3G kettles without an intermediate support pillar between the kettles. The tilting height from the pouring spout to the floor is 600 mm. An elevated installation frame is available and can be customised to the desired tilting height.

DELIVERY INCLUDES:

- a powerful stainless-steel mixing tool for all mixing, fitted with detachable and easy to clean scrapers - Heavy Duty mixing tool - a standard feature in 300 and 400 l combi-kettles
- a quick release stainless steel lid with a safety grid. Dishwasher safe. The rotating mechanism in the lid enables washing the lid even in the upright position while fixed to the kettle.
- stainless steel measuring stick, which is also dishwasher safe - support pillar
- accessory hook

OPTIONS (ordered together with the Proveno 4G combi-kettle)

- electronic or direct steam operated model
- hand shower with three options: S1 standard, Heavy Duty S2 or Reel-in Hand shower S3
- kettle sensor for wireless HACCP - Metos IoLiving
- automatic cooling C2, C3i or C5i; please see further details below
- drainage with pressurised air for C3iPA or C5iPA cooling
- draw off taps and valves D1 and D2
- double water connection; please see further details below
- foot switch, enabling mixing while tilting
- socket outlet (230V 10A) behind the control panel
- powerful high-performance heating element for 150 to 300 l kettles (requires a higher amperage inlet fuse)
- alternative voltages
- welded and seamless bowl cover is available for increased hygiene. Due to the fully welded outer surface, the whole device is urethane insulated ensuring excellent energy efficiency.

INSTALLATION OPTIONS

- fixed installation: with a sub-surface installation frame
- fixed installation: with a surface installation frame
- elevated installation frames are available for fixed installation
- free standing installation: frame and feet
- free standing, midfloor kit 1



- free standing, midfloor kit 2
- group installation accessories are available for all options above
- it is possible to fix a free-standing combi-kettle to the floor with installation flanges which do not penetrate into the floor surface. Installation flanges do not prevent moving of the kettle as necessary.

ACCESSORIES

- wireless IoLiving HACCP
- multi mixing tool with IoLiving sensor
- strainer plate
- strainer plate extension for 300 to 400 l kettles
- pouring adapter (spout reducer)
- whipping grid
- cleaning tool
- Heavy Duty Mixing tool for 150 to 200 l kettles
- blender lid kit Proveno 4G (40 to 100 l kettles)
- wide range of accessories for various cooking purposes

MATERIALS

The kettle is made entirely of stainless steel with inner surface of acid resistant stainless steel. Protection class: IPX5

CONTROL PANEL

- a large control panel is fully raised from the control pillar of the kettle and equipped with a touch screen
- the screen is protected from knocks as well as steam rising from the kettle
- informative and simple touch screen with various symbols and language options
- only available functions are active in the menu
- adjustable audio-visual signals
- info and error pop-up messages
- service diagnostics are available on the display
- clear and highly visible non-reflecting status display
- current status related user instructions are available on the touch screen
- IP68 protected USB connection in the back of the panel
- software updates via USB
- programs are saved and downloaded via USB
- HACCP data is saved via USB
- various user levels, for example, making changes in the programming requires logging in
- extensive kettle settings database which is managed by users
- demo mode for new users
- comprehensive demo application is available
- users may alter mixing patterns and create new programmes
- energy saving mode for touch screen
- emergency stop function

TIMER



- possibility to set several timers
- timed starting function (day/month/week)
- timed STOP-function
- Cook&Hold for maintaining desired temperatures
- egg timer
- timed heating
- timed mixing
- timed mixing patterns
- timed first water drainage
- timed adding of water

PROGRAMMING

- programming is as standard feature
- tested ready-to-use standard recipes and kettle cleaning programs
- programming, modifying and saving functions are available on the touch screen
- unlimited number of programs and program phases
- favourite pages for most popular programs
- HACCP set points and alarms
- timed starting function (day/month/week)
- new and customised mixing patterns also for kettle washing

CLEANING

Ready-to-use cleaning programs and possibility to save an unlimited number of customised cleaning programs. Washing tool is attached to the mixer. The chosen cleaning program doses an optimal amount of water, heats up the water and starts the mixer. Signal indicates the end of a program. Programs may be customised and copied for various washing needs.

SMART HEATING FUNCTION

ProTemp real-time temperature control allows setting food temperature, kettle jacket temperature, or their difference (Delta-T) on the basis of actual real-time temperatures to prevent the food from burning. Display for food and jacket real-time temperatures. Smart power setting enables sensitive cooking as well as cooking on full power. Delta-T cooking, low temperature cooking, sous vide, proving and tempering - with Proveno everything is possible. Temperature setting range of 0°C... 120°C with 1°C setting accuracy. Maximum operating pressure of 1.0 bar corresponds to + 120°C on the inside surface of the kettle. Optimal use of energy in all functions.

WATER AUTOMATIC, FOOD WATER FILLING

Automatic food water filling is a standard feature. Water is added via touch screen icons by choosing to open or close the tap, or by setting the amount of water to be added. Memory for added cooking water. Adding of cooking water may be adjusted by parameters with 100 ml intervals. Ideally located water-spout on the edge of the kettle enables filling of the kettle with water even when the kettle is being tilted, or with low water pressure. The possibility to add water when the kettle is being



tilted is extremely useful, for example, when cooking or rinsing pasta.

MIXER

Two directional mixing tool with an automatic reversing function provides thorough mixing at low speeds without Braking the product. Variable mixing speed for all kettle sizes is 15 to 140 rpm. Power mixing option is activated by touching and holding the respective icon, for example, for adding raw ingredients or spices. Mixing in a tilted position is enabled by touching and holding the icon when the kettle is being tilted. Pedal for mixing during tilting (optional) enables passing of the manually hand activated mixing during tilting. The pedal has two automated emergency stops.

The kettle has nine ready-to-use fully automatic mixing programs designed and tested by food-service professionals for healthy and versatile diets. You can also create and save your own mixing programs, for example, for Cold cooking, Hot-Fill and Cook Chilli cooking.

Standard mixing programs for this kettle:

- crumbling
- whipping
- mashing
- gentle stirring, for soups
- sautéing meat or vegetables and powerful back and forth mixing
- mashed potatoes and efficient back and forth mixing
- desserts
- porridges
- doughs

The mixer stops when the lid is opened. Mixing significantly decreases the time spent on heating and cooling which in turn helps to save energy.

TILTING

Efficient and long-lasting electric tilting for 40 to 150 l kettles, and hydraulic tilting mechanism for 200 to 400 l kettles. According to occupational safety standards, tilting of the kettle is enabled only when touching and holding the respective icon on the screen. Auto Tilt-back function stops the product flow from the kettle (may be adjusted with the respective settings) and makes working easier when filling containers. Additionally, this function increases safety when pouring hot product from the kettle. Ergonomic tilting height of the pouring spout is 600 mm from the floor enabling easier cleaning and emptying to bigger transport containers. An elevated installation frame is available for this kettle and can be customised according to the desired tilting height (optional).

AUTOMATED MONITORING

Integrated automatic monitoring. Automated monitoring data is saved on USB flash drive, or alternatively the kettle may be connected to, for example, the wireless Metos IoLiving system.



MEASURING OF ENERGY CONSUMPTION

Electric kettles are equipped with energy consumption measuring, and the results are available on the display. The data is als