

## Undercounter dishwasher Metos Premium 50 II HR DA



## **Product information**

SKU 4246489

Product name Undercounter dishwasher Metos Premium 50 II

HR DA

Dimensions  $600 \times 610 \times 850 \text{ mm}$ 

Weight 64,500 kg

Technical information 400 V, 6,65 kW, 3N, 50 Hz, 62 dB CW: 3/4"

Drain: ø 24mm

## **Description**

Metos Premium 50 II HR DA dishwasher with heath recovery and built-in water softener is a high performance glass & dishwasher. The new technology of the PREMIUM<sup>2</sup> line will lead you, in an easy and intuitive way, through the functions of your dishwasher. The soft-touch panel with the multicolor key and the TFT board shows clearly the working temperatures, the washing cycles and all functions in use. Thanks to its self-diagnostic system it notifies any anomaly. The innovative rinse-circuit, the six washing cycles, high quality performances, the possibility to easily modify their voltage make these machines extremely competitive and versatile.

## Equipped with heat recovery

The heat recovery pre-heats the incoming cold water with the heat produced by the machine. The immediate electricity cost savings with the heat recovery can be up to 35%. In addition the room temperature and the



amount of steam and moist is reduced.

- 8 washing programs: 6+2 cycles with partial tank drain before rinsing + two cycles with clean water
- M-Power multi-voltage connection function
- Intuitive Multi-Chromatic START key
- Electronic control with TFT display
- Easy-change voltage setting, directly from the cable connection
- Language selection of the menu control
- Wash pump 650 W
- Rinse pump 250 W
- Drain pump 25 W
- Tank volume 10 I / 7 I (partial drainage / clean water)
- Tank heating element 2,1 kW
- Water consumption / washing program 3.2 l / 7 l (glasses and dishes / clean water)
- Boiler volume 11 l
- Boiler heating element 6,0 kW
- Heat recovery
- Built-in water softener
- · Detergent dispenser
- Rinse aid dispenser
- ThermoStop temperature control continues the washing program until the set rinsing temperature is reached
- Rack size 500 x 500 mm
- Glass/Dishes max height 340 mm
- The round corners of the tank make cleaning easier
- Partial locking in the hatch
- HACCP Cloud-connection option (separate modem)