

Blast chiller tunnel Metos MBC201SB-RT



Product information

SKU	4240760
Product name	Blast chiller tunnel Metos MBC201SB-RT
Dimensions	1300 × 1400 × 2040 mm
Weight	446,000 kg
Capacity	150kg/+70...+3°C
Technical information	400 V, 10 A, 6,288 kW, 3NPE, 50 Hz
Type of the refrigerant	R452A/R448A/R449A
Cooling capacity [W]	5630
Condensing temperature [C]	+45
Evaporation temperature [C]	-25

Description

General features and functions of the Blast Chiller room Metos BC201SB-RT for trolleys

- capacity 20 x GN 1/1-40 or GN 10 x GN 1/1-65
- suitable for one GN 1/1 -trolley
- blast chilling
- two doors, roll through model
- inner measurements (length x depth x height) 680 x 950 x 1820 mm
- stainless steel construction
- floorless
- insulation made of high density polyurethane foam, thickness 80 mm

- copper-aluminum evaporator with cataphoresis anti-corrosion treatment
- high-ventilation evaporator to ensure the highest efficiency of the cooling system
- hinged door with gasket and closing ramp system
- vertical ergonomic door handle with magnetic closure
- rounded inner corners helps the cleaning
- inner bumpers in stainless steel
- fully inspectable front electric panel and IP54
- 7" high-definition IPS capacitive TOUCH display, easy to use
- high-performance evaporator fans - possibility to adjust the air flow in the blast chiller during chilling process
- USB port for HACCP data download, recipes and software update
- multipoint probe ensures an accurate chilling process by measuring the food core and surface temperatures
- possibility to program and save several customized chilling programs
- pre-cooling button ensures static blast chilling of food as soon as it is placed in the appliance
- after chilling process the machine automatically continues on the conservation phase
- chilling capacity 110 kg; stated blast chilling capacity kg/h is nominal, and cannot be achieved with all food products and circumstances
- for remote cooling, the cooling unit is not included in the delivery
- circuit breaker for compressor protection
- Class T (ambient temperature + 43 ° C)