

## Blast chiller room Metos MBC602SB-RI



### Product information

---

SKU	4240769
Product name	Blast chiller room Metos MBC602SB-RI
Dimensions	1500 × 3730 × 2040 mm
Weight	1 220,000 kg
Capacity	540kg/+70...+3°C
Technical information	400 V, 32 A, 18,364 kW, 3NPE, 50 Hz
Type of the refrigerant	R452A/R448A/R449A
Cooling capacity [W]	27960
Condensing temperature [C]	+45
Evaporation temperature [C]	-25

### Description

- for 3 GN 2/1 oven trolleys or 6 GN 1/1 trolleys
- floorless
- roll-in model
- inner depth 3350 mm
- door opening width 880 mm
- net height door 1820 mm
- chilling capacity 420 kg
- extraction capacity( -10 / + 45 ° C ) 52750 W
- panel construction
- stainless steel exterior (Scotch-Brite satin)



- inner in stainless steel with rounded corners
- inside bottom and floor die-formed leakproof
- insulation in high density (42 kg/m<sup>3</sup> approx.) expanded polyurethane, 80 mm thick, HCFC-free
- copper-aluminum evaporator with cataphoresis anti-corrosion treatment
- high-ventilation evaporator to ensure the highest efficiency of the cooling system
- anti-condensation resistance, placed on the door under the gasket
- hinged door with gasket and closing ramp system
- vertical ergonomic door handle with magnetic closure
- thick stainless steel internal bumper to avoid damage caused by the trolley
- external stainless steel protection to protect the control-board
- heated core probe, with 4 measuring points
- standard active chamber sterilization system with active ions (HI-GIENE) activated by the control
- pre-cooling function
- PLUS functions
- adjustment of the speed of the evaporator fans
- automatic storing at end of blast chilling
- indirect blowing electronic fans, efficient but gentle on food
- 7" high-definition IPS capacitive TOUCH display, easy to use
- processes identifiable through photos
- USB connection for uploading and downloading data and recipes
- circuit breaker for compressor protection
- electrical connections positioned frontally in the panel equipped with safety locks
- class T (ambient temperature + 43 ° C)
- remote condensing unit and possibility to have stainless steel protective cover