

Potwasher Metos Master KP152E TR PLUS with heat recovery



Product information

SKU	4246506
Product name	Potwasher Metos Master KP152E TR PLUS with heat recovery
Dimensions	690 × 800 × 2160/2275 mm
Weight	165,000 kg
Capacity	5-13 racks/hour
Technical information	400 V, 8,18 kW, 3NPE, 50 Hz, 64 dB HW: 3/4"

Description

The TR system is an heat exchanger: the moist warm water vapour is drawn directly out of the machine when the door is closed, and used for pre-heating the cold water supplied up to around 50°C. As a result, the energy required to reach the final rinse temperature (approx. 85°C) is dramatically reduced. The heat exchanger reduces the exhaust air temperature by more than an half. The entire humidity volume is cut down by approx. -20% of the equivalent machine without a heat recovery unit.

- potwasher with a door
- four washing cycles(3,5,7,9,11 min)
- ETR heat recovery condenses steam and it is not released into kitchen
- heat recovery saves energy even 5,5 kWh in cycle
- rack dimensions 550 x 665 mm, tray max height 805 mm
- free opening height 645 mm



- tank volume 50 l
- rinse aid dispenser
- self cleaning vertical pump
- deep-formed chair tank
- stainless steel independent wash/rinse arms
- double tank filter, with dirt collection system + pump filter
- thermostop to grant the rinse temperature according to HACCP regulations
- multichromatic START key
- automatic self-cleaning cycle
- double skinned door that can be used as a countertop