

Combi oven Metos LBES101 with 10 pair of guide rails



Product information

SKU	4571344
Product name	Combi oven Metos LBES101 with 10 pair of guide rails
Dimensions	930 × 825 × 1040 mm
Weight	174,000 kg
Capacity	10 x 1/1 GN
Technical information	400 V, 32 A, 16 kW, 3NPE, 50 Hz, 65 dB CW: 3/4" Drain: ø 40 mm

Description

Metos LBES101 is a sturdy and durable combination oven with boiler. A clear operating panel and easy-to-select functions combined with easy cleaning of the oven surfaces make the oven easy to use and clean.

The oven has 10 outlet pairs with outlet interval of 70 mm. The outlets can be used with GN1 / 1. The Metos LBES101 combination oven is electronically controlled and has three cooking modes: convection + 30 ° C ... + 300 ° C, steam + 30 ° C ... + 130 ° C and combined function + 30 ° C ... + 300 ° C.

The combination oven has a high visibility alphanumeric command display. Scroller knobs with Scroll and Push function make it easy to confirm choices. The automatic directional fan ensures a steady cooking result. Manual vapour extraction in the chamber as well as pre-heating.



The oven's structure is stainless steel. The smooth surfaces and watertight chamber, internal glass that fold to open make it easy to keep the device clean. Seven automatic cleaning programmes are available as well as the automatic cleaning system LCS. Calout descaling system that prevents the formation and build-up of limescale in the boiler.

The double-glazed, left-handed door is equipped with heat-reflecting slotted glasses that, together with the air gap between the glasses, reduce heat radiation while retaining heat inside the unit, avoiding unnecessary energy loss.

With USB connectivity, transferring HACCP data, update software and load/unload cooking programmes, is quick and easy.

- 10 outlet pairs, outlet interval 70 mm
- guides for GN1 / 1
- with boiler
- steam cooking + 30 °C to + 130 °C, convection air + 30 °C ... + 300 °C, combination function + 30 °C ... + 300 °C
- electronically controlled
- Scroller Plus knob
- Clima® automatic system for measuring and controlling humidity
- manual chamber vent
- Fast Dry® - System for quick dehumidification of the cooking chamber
- automatically regulated steam condensation
- halogen lighting in the oven chamber
- automatic reversing of the fan
- USB connection
- multipoint core probe Ø 3 mm
- door with double heat-reflective tempered glass with air gap, external glass mirrored effect
- internal glass folds open for easy cleaning
- left-handed door
- smooth watertight cooking chamber
- mechanical door switch
- 7 automatic cleaning programmes
- IPX5 water protection
- LCS automatic cleaning system

ACCESSORIES (ordered separately)

- hand shower
- stand
- various cooking pots and dishes
- right-hand door
- steam cooler hood
- shelf rack for baking plates 600x400mm