

Combi oven Metos LVET201 with 20 pair of guide rails



Product information

SKU	4571348
Product name	Combi oven Metos LVET201 with 20 pair of guide rails
Dimensions	960 × 825 × 1810 mm
Weight	260,000 kg
Capacity	20 x 1/1 GN
Technical information	400 V, 60 A, 31,8 kW, 3NPE, 50 Hz, 65 dB

Description

Metos LVET201 combination oven with direct steam has a clear control panel with shortcut and easy-to-select functions combined with easy cleaning of the oven and oven surfaces to facilitate and enhance the day-to-day operation of the kitchen. The precise temperature and humidity control of the oven chamber makes the food tasty, while retaining its color and texture, also allowing for frying and grilling.

The oven includes a trolley with 20 outlet pairs and outlet interval of 63 mm. The outlets can be used with GN1 / 1 pans. The Metos LVET201 combination oven has three cooking modes: convection from + 30 ° C ... + 300 ° C, steam from + 30 ° C ... + 130 ° C and combined function + 30 ° C ... + 300 ° C. The oven has automatic system for measuring and controlling the humidity in the cooking chamber. All programmes in the memory can be linked to shortcuts and create a favourite list.

The oven's structure is stainless steel. The smooth surfaces and watertight chamber, internal glass that fold to open make it easy to keep the device clean. Seven automatic wash programmes are available as well as the automatic cleaning system LM.

The oven has an LCD-TFT color display for displaying favorite programs, preset programs, menus and settings. With the help of the scroller knob, it makes it easy to manage programmes and select cooking stages. The double-glazed, left-handed door is equipped with heat-reflecting slotted glasses that, together with the air gap between the glasses, reduce heat radiation while retaining heat inside the unit, avoiding unnecessary energy loss. With USB connectivity, transferring HACCP data and cooking programmes, as well as updating your operating system, is quick and easy.

- trolley with 20 outlet pairs, outlet interval 63 mm
- rails for GN1 / 1
- direct steam
- steam cooking + 30 °C to + 130 °C, convection air + 30 °C ... + 300 °C, combination function + 30 °C ... + 300 °C
- programmable with the ability to store cooking programmes in automatic sequence
- automatic temperature and humidity control system Clima®
- easy access to programmable user parameters
- Fast Dry® - System for quick dehumidification of the cooking chamber
- LED lighting in the oven chamber
- automatic reversing of the fan
- LCD-TFT color display
- Scroller Plus knob
- USB connection
- Temperature control at the product core using probe with 4 detection points
- Core probe connection through a connector outside of the cooking chamber
- door with double heat-reflective tempered glass with air gap
- internal glass folds open for easy cleaning
- left-handed door
- smooth watertight cooking chamber with rounded edges
- mechanical door switch
- LM automatic cleaning system
- 7 automatic cleaning programmes
- IPX5 water protection

ACCESSORIES (ordered separately)

- hand shower
- needle-shaped cooking sensor
- energy optimisation system
- stand
- various cooking pots and dishes
- shelf rack for baking plates 600x400mm