

Deep chiller Metos Start MDC50R R290



Product information

SKU	4247520
Product name	Deep chiller Metos Start MDC50R R290
Dimensions	600 × 700 × 2080 mm
Weight	110,000 kg
Capacity	25-28 kg/4h (+60 C -> +6 C)
Technical information	230 V, 10 A, 1,26 kW, 1NPE, 50 Hz
Type of the refrigerant	R290
Quantity of refrigerant [g]	150

Description

Deep chiller Metos Start MDC50R is intended for fast thawing of hot food. Refrigerated foods can be transferred directly to GN containers for cabinet shelving. At the end of the cooling process, the appliance automatically switches to a refrigerator.

The cooling cabinet Metos Start MDC50R cooling capacity is 5xGN1/1 dishes and cools 25-28 kg + 65°C to + 6°C in 240 minutes, 16-18 kg + 65°C to +10°C in 120 minutes (capacity is a guideline and cannot be achieved with all food items or under all circumstances). The machine automatically transfers to storage space after the end of the cooling process. The refrigerated cabinet can also be used as a refrigerator.

The cooling cabinet has five GN1 / 1-rated shelving lead pairs. Leads

are easily detached for transfer and cleaning of the cabinet, setting distance in 50 mm. Shelves are available as an accessory.

It is easy to clean the unit with its stainless steel construction, rounded inner pockets and easy-to-detach leads. In addition, the unit is equipped with automatic defrosting and evaporation of mildew, as well as the possibility of manually starting defrosting.

The device has a right-hand door with a sealant that is easily replaceable. The lockable, self-closing door remains open when opened at a 90° angle. The refrigerator cabinet is located at the top of the cabinet. The display shows alarm information about possible setpoint temperature and overrun.

- right-hand lockable door
- the cooling cabinet cooling capacity is 25-28 kg +65°C...+6°C in 240 minutes, 16-18 kg +65°C...10°C in 120 minutes (capacity is a guideline and can not be achieved with all food items or under all circumstances).
- after the programme is ended, the machine automatically transfers to storage space (+2°C...+4°C)
- 5 shelf lead pairs for GN1/1-containers
- leads are easily detached
- automatic defrosting and evaporation of drain water
- stainless steel inner and outer lining
- 75 mm CFC- and HCFC-polyurethane insulation
- rounded inner corners
- stainless steel adjustable feet
- EVJ controller
- air-condensed
- refrigerant R290

ACCESSORIES (ordered separately):

- additional lead pair
- shelves
- foot pedal