

Rack conveyor machine METOS WD-11 TOUCH R-L



Product information

SKU 4246273

Product name Rack conveyor machine METOS WD-11 TOUCH R-

L

Dimensions $1355 \times 697 \times 1675/1950 \text{ mm}$

Weight 280,000 kg

Capacity 56 baskets/hour (DIN 10510)

Technical information 400 V, 35 A, 19,7 kW, 3NPE, 50 Hz, 68 dB

HW: R1/2" Drain: ø 50 mm

Description

The Metos WD-11 TOUCH is a simple, compact, and flexible rack conveyor machine with a medium capacity that delivers excellent wash results. A small, simple rack conveyor machine for use when the capacity of a single-tank dishwashing machine is not sufficient. The symbols on the control panel are easy to follow and give the user relevant information about washing, rinsing temperatures, alarms and more. Thanks to the heating and sound insulation, the surface temperature and noise levels are kept to a minimum, helping to achieve a good working environment. The machine comes with a chemical washing zone, a dual final rinse, and an electronic control system as standard.

The WD-11 has unique basket feed system which allows for a flexible operator contact time. The recommended capacity is 50 to 85 baskets per hour, which the operator can adjust depending on how dirty the loads



are.

The machine's surfaces are smooth to make it easy for the operator to clean and maintain. The large, well-balanced sliding doors make all the washing areas easily accessible. The doors can also be removed to allow the back of the machine to be cleaned.

- feeding direction right-left
- Infeed size 538'440mm
- · Contactor for entry and exit conveyor

OPTIONS

- Marine version 400/3/50Hz without neutral
- Marine version 440/3/60Hz without neutral
- Back flow protection according to EN 1717.
- · Break tank included with booster pump
- Booster heater 9 kW for re-circulating final rinse
- Booster heater 9 kW for cold water connection
- Water connection from floor
- Stainless pipes and couplings in final rinse
- Timer for pre-rinse
- Timer for through-rinse
- Timer for chain-rinse
- Contactor for control of pre-rinse without timer
- Contactor for pre-rinse with booster pump

WEIGHT,,280 kg DIMENSIONS,,1355 \times 697 \times 1685/1950 mm CAPACITY,,50-100 racks/hour

TECHNICAL INFORMATION,, 400 V, 35 A, 19,7 kW, 3NPE, 50 Hz, 68 dB CW: 1/2" HW: R1/2" Drain: ø 50 mm